



8770 W 28 Rd. Harrietta, MI 49638	
Phone: 269.751.8898	topgradesmc.com

Product	W40-70
Plant	Top Grade: Wexford Sand
Date	December 26th, 2025

Specification	
U.S. Mesh	Typical
30	0.0
40	0.8
45	11.9
50	33.1
60	36.5
70	17.5
100	0.2
Pan	0.0

Properties	
LOI	0.140
NTU	59.20
Roundness	0.827
Sphericity	0.441
Bulk Density (pcf)	90.50

Crush	
Stress Level (PSI)	
7K	9.0%
8K	11.9%

GFN	38.0
Accum %	96.1%

Quality / Technical Assurance Representative	
Andy Swett	December 26th, 2026

Silica, Lake Sand Products



DANGER

MAY CAUSE CANCER IF INHALED. CAUSES DAMAGE TO LUNGS, KIDNEYS AND IMMUNE SYSTEM THROUGH PROLONGED OR REPEATED EXPOSURE BY INHALATION

These products have been classified, following the Globally Harmonized System (GHS) of Classifying and Labeling Chemicals criteria, as a Category 1A Carcinogen, and a Category 1 Specific Target Organ Toxicity (following repeated exposures). For Industrial Use Only. DO NOT USE THIS PRODUCT FOR BLASTING. DO NOT BREATHE DUST. PRODUCT CAN ACCUMULATE ELECTROSTATIC CHARGES DUE TO FRICTION FROM TRANSFER AND MIXING OPERATIONS AND CAUSE AN ELECTRICAL SPARK (IGNITION SOURCE). Read the specific Safety Data Sheet (SDS) before using and follow applicable local, state and federal health and safety standards.